

DOWNLIGHT SYSTEM / SPOT SYSTEM

Ceiling cutout [mm]	COBs					Directional spotlight		Spots		Downlights		Wallwasher	Installation variants				Lighting technology	Electronics		
	High colour rendering quality	High efficiency	High colour rendering quality	High efficiency	High efficiency	Directional spotlight	Directional spotlight	medium flood 24°	flood 36° fixed	very wide flood 60°	extremely wide flood 80°	wallwash	Plaster ring IP20	Cover ring IP20/54	Surfacemount housing IP20	Suspended housing IP20	Flux [lm]	UGR 19	DALI	Live Link ready
68	✓	✓	✓	✓	✓	●○●●	●○●●	●○●●	●○●●	●○●●		●○●●	01	01, 03, 05			800	✓	✓	✓
100	✓	✓	✓	✓	✓	●○●●	●○●●	●○●●	●○●●	●○●●		●○●●	01	01, 03, 05			800	✓	✓	✓
150	✓	✓	✓	✓	✓	●○●●	●○●●	●○●●	●○●●	●○●●	●○●●	●○●●	01	01, 03, 05	01, 03, 05	01, 03, 05	1400	✓	✓	✓
210		✓	✓	✓	✓							●○●●	01	01, 03, 05	01, 03, 05	01, 03, 05	2000	✓	✓	✓
												●○●●	01	01, 03, 05	01, 03, 05	01, 03, 05	2600	✓	✓	✓
												●○●●	01	01, 03, 05	01, 03, 05	01, 03, 05	2600	✓	✓	✓
												●○●●	01	01, 03, 05	01, 03, 05	01, 03, 05	3800	✓	✓	✓

● black ○ white ● semi-specular ● highly specular □ Surface-mounted and suspended luminaires
 01 white 03 silver 05 black □ Emergency light

NAMING CONVENTION

SNS ACT R C 1 - 2R HR R MF - 19 - IP 8 - 940 ETDD EB3 X1 01

Product name	HCL mark (optional)	Construction form	Installation method	Construction size	Suspension height	Reflector	Reflector addition (optional)		Light distribution	UGR	Protection rating (optional)	System luminous flux	Light colour/ CRI	Switching type	Emergency light (optional)	Connectivity (optional)	Frame colour/ housing colour
SNS	ACT	R - round Q - square	C - recessed, with edge T - recessed, edgeless D - ceiling surface-mounted H - suspended	1 - 68 mm 3 - 100 mm 5 - 150 mm 7 - 210 mm	2R - 2 m round ceiling rose 2Q - 2 m square ceiling rose	HR - highly specular MR - frosted WR - white SR - black	R - directional spotlight W - wallwasher		MF - medium flood (24°) FL - flood (36°) VFL - very wide flood (60°) XFL - extremely wide flood (80°)	19 22	IP - IP54	8 - 800 14 - 1400 20 - 2000 26 - 2600 38 - 3800	830 840 927 930 940	ETDD ET	EB3 - 3h remote emergency	X1 - AL, GST5 X2 - AL, GST3	01 - white 03 - silver-colour 05 - black